



GyroScout[™]

Slim and compact continuous measurement gyro. Ideal for blast hole measurement

Reduce downtime and deliver accurate results



GyroScout™

Technical Specifications

Dimensions		Battery	
Length	950 mm (37,4")	Battery Type	
Outer Diameter	32 mm (1,25")	Operating Time	
Weight	2,6 kg (5,73 lbs)		
Operational Environment		Data	
Operational Environment	0000	Communications	
Depth Pressure	2900 psi	Export	
Operational Temperature	-10°C - +60°C	ΣΑΡΟΤ	
	(+14°F - +140°F)	Export Format	
		Graphic Generation	
Performance*		Survey Report	
Azimuth Range	0° - 360°		
Inclination Range	-90° - +90°		
Azimuth Accuracy	0,16°	Handheld Device	
Inclination Accuracy	0,05°	Battery	
Typical Positional Accuracy	0,3%**	IP Rating	

^{*} Accuracy quoted at 1σ

Maximum lightness without loss of accuracy

At only 32 millimeters in diameter and 950 millimeters in length, *GyroScout*™ is one of the lightest, most portable and robust gyroscopes on the market. at 2.4 kg weight, it helps you to minimise time and optimise effort in survey operations.

Automated and intuitive software

The software used to control the *GyroScout*[™] is intuitive, simple and powerful at the same time, and includes the option of exporting detailed reports in the most widely used formats in the industry: PDF, Excel, CSV, LAS and DXF. The tool can instantly synchronize data in the cloud thanks to its native support for SPT *SmartCloud*[™] which allows you to manage and store measurements from all mining projects with complete security and data protection.

Handy and versatile design

GyroScout™ is a versatile tool; its rugged design allows it to operate at all angles in the most adverse conditions. It is the industry's smallest gyro with integrated pressure barrel. An optimal solution for blasting operations.

EUROPE	AFRICA	NORTH AMERICA	SOUTH AMERICA		ASIA-PACIFIC	EURASIA
Sweden (HQ)	South Africa	Canada	Argentina	Ecuador	Perth Australia	Armenia
+46 (8) 590 733 10	+34 (952) 179 918	+1 (877) 594 4633	+54 (9) 261 623 1542	+593 (99) 200 1060	+61 861 156 379	+374 (77) 815 683
+34 (952) 179 918	Ghana	USA	Brazil	Peru	Indonesia (Mining)	Kazakhstan
Spain (HQ)	+233 555 956 594	+1 (281) 460 5508	+55 (31) 996 254 379	+ 51 982 505 682	+62 (811) 11 8 1608	+7 (705) 160 2241
+34 (952) 179 918		Mexico (North)	Chile (Santiago)	Bolivia	Indonesia (O&G)	
Ukraine		+52 (662) 110 0219	+56 (9) 8238 2609	+591 7 721 2107	+62 (812) 9100 651	
+38 (067) 562 91 69		+52 (662) 229 4755	Colombia			
Turkey		Mexico (South)	+57 (311) 531 1609			
+90 (533) 334 54 53		+52 (662) 430 7255				



Lithium Ion Rechargeable

SPT SmartCloud via WIFI

PDF, Excel, CSV, LAS, DXF

24 hrs

Bluetooth®

or 4G LTE

At any interval

IP68, IP69K

4/6 hrs (8580 mAh)

2D, 3D

^{**} Well profile dependent.